

StealthNet™

with 12v CN-Linko Adaptor



Installation Guide

Kit Includes:



StealthNet Gateway



12V Adaptor

Professional Installation Recommended - Installation of EZTrac HE is recommended to be installed by a professional installer that has sufficient technical knowledge and expertise for mobile device installation and integration with commercial assets. i.e. Certified Geotab Installer certification or equivalent.



Remove Hibernation Plug From Device

The Phillips Connect StealthNet™ comes with an attached hibernation plug, keeping the device in ship mode to prevent depletion of the battery during shipping. To activate, pull the yellow hibernation plug off from the bottom of the device.

Connect Automatically or Connect With 12V Adaptor

StealthNet™ can connect automatically or via the provided 12V adaptor which additionally charges the device's internal battery.



Notice: Once installed, do not pressure wash the device or the immediate surrounding area.

To connect via the 12V adaptor, plug and twist the 12V adaptor to the bottom of the StealthNet™ device until it securely locks in. Once locked, plug the other end of the 12V adaptor into any automobile auxiliary power outlet.

Device Lighting Guide -

- Red Light Flashing - GPS Search
- Solid Red Light - GPS Found
- Amber Light Flashing - Message Pending
- Green Light Flashing - Cellular Search
- Solid Green Light - Cellular Connected